

Activated Carbon & Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA

Toll Free: (800) 394-6844

Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242

www.cameroncarbon.com • sales@cameroncarbon.com

## CE6P

Cameron type CE6P is a high quality coal based extruded activated carbon suitable for a wide range of general vapor phase applications. In addition to a very highly developed internal structure this product also offers excellent mechanical strength and uniform particle size distribution. Standard packaging is in 200 lb drums, 50 lb bags or 1,000 lb bulk bags.

Mesh Size 4 mm diameter pellet

Carbon Tetrachloride Activity 60% w/w minimum

Moisture Content (as packed) 5% w/w maximum

Hardness Number 97 minimum

Apparent Density 0.50 g/mL minimum

lodine Number 875 mg/g minimum

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.