

# Cameron Carbon

INCORPORATED

Activated Carbon  
& Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA  
Toll Free: (800) 394-6844  
Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242  
www.cameroncarbon.com • sales@cameroncarbon.com

## CG6 8x30

Cameron type CG6 is a high activity granular activated carbon manufactured from a carefully selected grade of high quality bituminous coal. It is activated under rigidly controlled conditions to ensure consistency in quality. It exhibits a well developed pore structure, excellent mechanical strength and a high Iodine Number. It is particularly recommended for use in high grade water treatment applications, food & pharmaceuticals, purification of acids, caustic liquors, plasticizers, soda ash and fatty acids. Packaging is in 50 lb bags, 200 lb drums or 1,000 lb bulk bags.

Mesh Size	>8 15% maximum <30 4% maximum
Iodine Number	920 mg/g minimum
Moisture Content (as packed)	2% w/w maximum
Molasses Number	240 average
Abrasion Number	80 average
Bulk Density	30 lb/ft <sup>3</sup> average
Ash Content	12% w/w average

*This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent invention.*