

Cameron Carbon

INCORPORATED

Activated Carbon
& Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA
Toll Free: (800) 394-6844
Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242
www.cameroncarbon.com • sales@cameroncarbon.com

CG6/AW 12x40

Cameron type CG6/AW is a high activity granular activated carbon manufactured from a carefully selected grade of high quality bituminous coal. It is activated under rigidly controlled conditions to ensure consistency in quality. It exhibits a well developed broad pore size spectrum, excellent mechanical strength and a high Iodine Number. CG6/AW is acid washed in order to minimize leachable metals and for pH adjustment. It is particularly recommended for use in high grade water treatment applications, food & pharmaceuticals, purification of acids, caustic liquors, plasticizers, soda ash and fatty acids. Packaging is in 50 lb bags, 200 lb drums or 1,000 lb bulk bags.

| | |
|------------------------------|-------------------------------|
| Mesh Size | >12 5%, <40 4% maximum |
| Iodine Number | 1,000 mg/g minimum |
| Moisture Content (as packed) | 5% w/w maximum |
| Abrasion Number | 80 average |
| Bulk Density | 30 lb/ft ³ average |
| Molasses Number | 240 average |
| Ash Content | 8% w/w maximum |
| Effective Size | 0.55— 0.75 mm |
| Uniformity Coefficient | 1.9 maximum |

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.