

Activated Carbon & Related Technology

P.O. Box 995 Havre de Grace MD 21078 USA

Toll Free: (800) 394-6844

Tel: +1 (410) 942-0240 • Fax: +1 (410) 942-0242

www.cameroncarbon.com • sales@cameroncarbon.com

PACarb Plus

Cameron type PACarb Plus is a high quality powdered activated carbon manufactured from carefully selected grades of a resinous wood charcoal and high quality coal. It is activated in a rigidly controlled oxygen-rich atmosphere to ensure consistency in quality. It exhibits a well developed broad pore size spectrum and excellent adsorption characteristics. It is particularly recommended for use in municipal water treatment plants in the production of drinking water. PACarb Plus complies fully with AWWA B600-90 specification and is certified in compliance with ANSI/NSF Standard 61. Standard packaging is in 50 lb bags, 1,000 lb bulk bags or bulk road/rail containers.

Wet Screen Analysis 90% <325 minimum

lodine Number 800 mg/g average

Moisture Content (as packed) 10% w/w maximum

Bulk Density 26 - 30 lb/ft³

Apparent Density 0.42 - 0.48 g/mL

Tannin Value 400 mg/L maximum

pH 6-8

Phenol Number 2.0 g/L

Ash Content 10 % w/w maximum